

NVENT ERIFLEX ZIPFLEX SLEEVE



- Quick and easy screening
- Installation tool included
- Halogen free

Material: Polypropylene

Color: Black

Working Temperature: -30 to 140 °C

Flammability Rating: UL® 94HB



Part Number	Article Number	Diameter	Length	Unit Weight
ZFX100M8MMBK	554880	8 mm	100 m	0.015 kg
ZFX50M15MMBK	554890	15 mm	50 m	0.044 kg
ZFX30M20MMBK	554900	20 mm	30 m	0.070 kg
ZFX20M25MMBK	554910	25 mm	20 m	0.100 kg

Unit weight is per meter (3.28').

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent. All rights reserved.

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.