

STAINLESS STEEL FLOOR STANDING

Features

- IP66
- 316 stainless steel
- Body construction 1.5mm
- Universal enclosure
- Adjustable inner door kits and escutcheon options
- Concealed stainless steel hinges
- Fully welded construction
- Polyurethane gasket
- Padlockable 3 point locking system
- 3mm aluminium gland plate
- Stainless steel mounting plinth
- Mounting pan 2mm powder coated white mild steel
- Earth strap kit

Options

- Door rails (CI)
- Gland plates (CI)
- Vent kits (CI)
- Windows (CI)



Typical Applications



Floor Standing Enclosure Selection Table

| Model No. | Height | Dimensions (mm) | | Useable Depth |
|-------------|--------|-----------------|-------|---------------|
| | | Width | Depth | |
| PSFS1806030 | 1800 | 600 | 300 | 282 |
| PSFS1806040 | 1800 | 600 | 400 | 382 |
| PSFS1808040 | 1800 | 800 | 400 | 382 |
| PSFS1806050 | 1800 | 600 | 500 | 482 |
| PSFS1808050 | 1800 | 800 | 500 | 482 |
| PSFS2006050 | 2000 | 600 | 500 | 482 |
| PSFS2008040 | 2000 | 800 | 400 | 382 |
| PSFS2008050 | 2000 | 800 | 500 | 482 |