


**Model PVLEAD3**  
**MC4 Solar Clamp Test Lead Set****Features**

- Set of black and red MC4 Solar Power Clamp Test Leads
- The black test lead is a MC4 (male) breakout to 12-inch MC4 (female) and 36-inch 4mm sheathed banana plug test lead
- The red test lead is a MC4 (female) breakout to 12-inch MC4 (male) and 36-inch 4mm sheathed banana plug test lead
- Designed for use with Solar Clamp Meters that accept 4mm sheathed banana plugs
- Creates connection between the Solar Panel and Inverter for measuring with a Clamp Meter
- Ensures safe DC power measurements on Photovoltaic (PV) modules and systems
- Allows user to monitor solar PV circuits during operation for troubleshooting and maintenance of PV systems
- Nickel plated contacts

**Ratings**

Voltage: Complies to IEC / EN 61010-031  
CAT III 1000V / CAT IV 600V  
Do Not Disconnect Under Load

Current: 20A

Temperature Range: +5°C to +40°C

**Ordering Information**

Model: PVLEAD3

MC4 SOLAR POWER CLAMP SET

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm 0.02$ " (.51 mm),  
.xxx =  $\pm 0.005$ " (.127 mm). All specifications are to the latest revisions.  
Specifications are subject to change without notice. Registered trademarks are  
the property of their respective companies.

Copyright © 2021 D2169353 Rev. 003

Page 1 of 1